



ALLTECH BOHEMIA
Cable - Lubricant

Alltech Bohemia CB a.s.
J.Lomského 777/13
CZ 370 06 Č. Budějovice 5
T 00420 384 794586
F 00420 384 794584
albo@abcb.eu
www.abcb.eu



STTE-GL-70

TECHNICAL INFORMATION

STTE-GL-70 increases the sliding properties for all cable laying work and also for cable deinstallation work in building services as well as laying telephone cables and cables for intrusion alarm systems.

STTE-GL-70 does one 70% friction loss.

Due to its ease of use, its flowability and its smoothness, it is recommended for the installation of cables in building services.

- **STTE-GL-70** is a water-based lubricant.
- **STTE-GL-70** solves all friction problems generated when inserting and removing wiring from domestic systems.
- **STTE-GL-70** retains its lubricating power even years after application.
- **STTE-GL-70** protects cables from ageing.
- **STTE-GL-70** is compatible with all types of cable.

Use: when installing new wiring systems, spray **STTE-GL-70** directly onto the wires before inserting them or, alternatively, pour **STTE-GL-70** into the conduit pipe before inserting the wires.

To remove wiring pour **STTE-GL-70** directly into the conduit pipe, wait a few moments for the product to reach the point of friction, and then pull the wire out.

To insert new wires into existing wiring systems, pour **STTE-GL-70** directly into the conduit pipe before installing the new wires.

Warning during use: avoid contact with marble, carpeting, parquet flooring, etc. If the product does come into contact with surfaces it can be removed using a normal stain remover for fabrics.

TECHNICAL SPECIFICATIONS

Appearance	milky liquid
Odor	odorless
Viscosity at 20C°	very fluid
Specific weight	0,990 gr/cm3
pH	7
Flammability	not flammable
Usage temperature	-10 - +40° C.
Toxicity	non-toxic
WGK	1 (according to 2000 German and British standards)
PACKAGING	
Cod. STTE-GL-70.05	500g bottles in cardboard boxes each containing 12 bottles
Art.-No 7600100	