



Cable Lubricant Liquid STTE-GL-70

Application:

STTE-GL-70 increases the sliding properties for all cable laying work and for cable deinstallation work in building technology as well as for laying telephone cables and cables for burglar alarm systems.

STTE-GL-70 makes a 70% friction loss.

Due to its ease of use, its fluidity and its smoothness, it is recommended for the installation of cables in building technology.

How using STTE-GL-70:

When installing new cabling systems, spray STTE-GL-70 directly onto the wires before inserting them or, alternatively, pour STTE-GL-70 into the cable conduit before pulling in the cables.

To remove wiring, STTE-GL-70 is poured directly into the installation pipe. Wait a few moments until the product has reached the point of friction and then pull out the cable.

To introduce new cables into an existing cabling system, you pour STTE-GL-70 directly into the conduit before installing the new cables.

Important note during use: Avoid contact with marble, carpeting, parquet, etc. If the product comes into contact with these surfaces, it can be removed with a standard fabric stain remover.

Head:
ALLTECH BOHEMIA CB a.s.
J. Lomského 777/13
370 06 České Budějovice 5
www.abcb.eu
Česká republika

Stock:
ALLTECH BOHEMIA CB a.s.
Hospodářský park čp 555
378 10 České Velenice
albo@abcb.eu
Česká republika

No. 7600100

e 500g