



## Cable Lubricant STTE-GL-90

### Field of use:

STTE-GL-90 reduces friction when installing power, telephone, coaxial and fiber optic cables (fiber optic cable installation requires a custom application) by up to 90%. Suitable for installation for long power cables (6000m) and for pre-lubrication for installation in plastic pipes.

Recommendation: When laying fiber optic cables, pipes should be pre-lubricated. Also suitable for cable machines. When used in automated compressed air systems, the lubricant consumption is significantly reduced.

### Properties:

STTE-GL-90 is non-toxic, biodegradable (95% pure) and non-flammable.

Semitransparent, soap-smelling greenish liquid.

Operating temperature: -20 ° C to + 65 ° C

- > STTE-GL-90 achieves its lubricating effect even after use.
- > STTE-GL-90 protects the cable against aging.
- > STTE-GL-90 seals perfectly on the cable surface.
- > STTE-GL-90 retains its lubricating performance even in the presence of water.
- > STTE-GL-90 can be used for all cable types.

Consumption with STTE-GL-90: 50 to 10 grams per linear meter.

Consumption is significantly reduced with automated compressed air system.

Distribution:  
ALLTECH BOHEMIA CB a.s.  
J. Lomského 777/13  
370 06 České Budějovice 5  
www.abcb.eu  
Česká republika

Stock:  
ALLTECH BOHEMIA CB a.s.  
Hospodářský park čp 555  
378 10 České Velenice  
sales@abcb.eu  
Česká republika

**No. 7600110**

**e 500g**